



EXCHANGER SIZE *-BAFFLE SPACING	DIMENSIONS											
	A		B		C		D		N1		N2	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
W-103-2*-2	49 5/8	1260	23 1/2	597	10 1/2	267	38	965	6	152	6	152
W-104-2*-2	61 5/8	1565	35 1/2	902	22 1/2	572	50	1270	6	152	6	152
W-105-2*-2	73 5/8	1870	47 1/2	1207	34 1/2	876	62	1575	6	152	6	152
W-106-2*-2	85 5/8	2175	59 1/2	1511	46 1/2	1181	74	1880	6	152	6	152
W-107-2*-2	97 5/8	2480	71 1/2	1816	58 1/2	1486	86	2184	6	152	6	152
W-108-2*-2	109 5/8	2784	83 1/2	2121	70 1/2	1791	98	2489	6	152	6	152
W-109-2*-2	121 5/8	3089	95 1/2	2426	82 1/2	2096	110	2794	6	152	6	152
W-1010-2*-2	133 5/8	3394	107 1/2	2731	94 1/2	2400	122	3099	6	152	6	152
W-1011-2*-2	145 5/8	3699	119 1/2	3035	106 1/2	2705	134	3404	6	152	6	152
W-1012-2*-2	157 5/8	4004	131 1/2	3340	118 1/2	3010	146	3708	6	152	6	152
W-1013-2*-2	169 5/8	4308	143 1/2	3645	130 1/2	3315	158	4013	6	152	6	152
W-1014-2*-2	181 5/8	4613	155 1/2	3950	142 1/2	3620	170	4318	6	152	6	152
W-1015-2*-2	193 5/8	4918	167 1/2	4255	154 1/2	3924	182	4623	6	152	6	152

NOZZLE SCHEDULE				
SERVICE	MARK	SHELL SIDE	MARK	TUBE SIDE
INLET	N1	AS PER TABLE	N5	4 (102) FLG
OUTLET	N2	AS PER TABLE	N6	4 (102) FLG
DRAIN	N3	1/2 (13) NPT		
VENT	N4	3/4 (19) NPT		

NOTES: 1. SUPPORTS SUPPLIED ONLY IF SPECIFIED ON ORDER.  
 2. NOZZLE SIZES SHOWN ARE RECOMMENDED FOR MAXIMUM EXCHANGER LIFE.  
 3. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.  
 4. DRAWING IS NOT TO SCALE.  
 5. ALL DIMN'S ±1/8 (3) UNLESS OTHERWISE SHOWN.

DESIGN CONDITIONS				
	SHELL		TUBES	
DESIGN PRESSURE	150 PSIG	1034 KPa	150 PSIG	1034 KPa
DESIGN TEMPERATURE	375 °F	191 °C	375 °F	191 °C
MIN. DESIGN METAL TEMP.	35 °F	1.7 °C	35 °F	1.7 °C
HYDRO. TEST PRESSURE	225 PSIG	1551 KPa	300 PSIG	2068 KPa
CONTENTS	WATER		WATER	

CUSTOMER:  
 LOCATION:  
 ENGINEER:  
 ORDER No.:  
 PROJECT/JOB:  
 LOCATION:  
 TAG: (QUOTE # )

TITLE	G.A. 150 LB. W SERIES HEAT EXCHANGERS	A R M S T R O N G				NUMBER	W-10-2P-2(6)	REV.
DATE:	12 / 01 / 94	BY:	D.C.R.	TEL: (416) 755-2291	TEL: (514) 421-2424	TEL: (716) 693-8813	TEL: (44) 120-657-9491	