



DIMENSIONS SHOWN AS: inches (mm)

EXCHANGER SIZE	DIMENSIONS								NOZZLE SCHEDULE		
	"A"		"B"		"C"		"D"		"N1"		
	Inches	mm	Inches	mm	Inches	mm	Inches	mm			
THW-2030-2-4	50 -3/8	1280	29-1/2	749	33	838	13-3/8	340	N1	INLET	8" FLG (203)
THW-2036-2-4	56 -3/8	1432	35-1/2	902	39	991	19-3/8	492	N2	OUTLET	8" FLG (203)
THW-2042-2-4	62 -3/8	1584	41-1/2	1054	45	1143	25-3/8	645	N3	DRAIN	1/2" NPT (13)
THW-2048-2-4	68 -3/8	1737	47-1/2	1207	51	1295	31-3/8	797	COLLAR ASSEMBLY		
THW-2054-2-4	74 -3/8	1889	53-1/2	1359	57	1448	37-3/8	949		STANDARD	OVS. FOR STONE LINING
THW-2060-2-4	80 -3/8	2042	59-1/2	1511	63	1600	43-3/8	1102	"E"	20" (508)	22" (559)
THW-2066-2-4	86 -3/8	2194	65-1/2	1664	69	1753	49-3/8	1254	"F"	14" (254)	16-1/2" (419)
THW-2072-2-4	92 -3/8	2346	71-1/2	1816	75	1905	55-3/8	1407	DESIGN CONDITIONS		
THW-2078-2-4	98 -3/8	2499	77-1/2	1969	81	2057	61-3/8	1559	TUBES		
THW-2084-2-4	104-3/8	2651	83-1/2	2121	87	2210	67-3/8	1711	DESIGN PRESSURE	150 PSIG	1034 KPa
THW-2090-2-4	110-3/8	2804	89-1/2	2274	93	2362	73-3/8	1864	DESIGN TEMPERATURE	375 F	191 C
THW-2096-2-4	116-3/8	2956	95-1/2	2426	99	2515	79-3/8	2016	M.D.M.T.	40 F	4.4 C
THW-20102-2-4	122-3/8	3108	101-1/2	2578	105	2667	85-3/8	2169	HYDRO TEST PRESSURE	225 PSIG	1551 KPa
THW-20108-2-4	128-3/8	3261	107-1/2	2731	111	2819	91-3/8	2321	NOTES:		
THW-20114-2-4	134-3/8	3413	113-1/2	2883	117	2972	97-3/8	2473	1. COLLAR ASSEMBLY SUPPLIED SEPARATELY.		
THW-20120-2-4	140-3/8	3566	119-1/2	3035	123	3124	103-3/8	2626	2. FABRICATED TO ASME CODE SECTION VIII DIVISION 1 AND LATEST ADDENDA.		
THW-20126-2-4	146-3/8	3718	125-1/2	3188	129	3277	109-3/8	2778	3. DRAWING IS NOT TO SCALE.		
THW-20132-2-4	152-3/8	3870	131-1/2	3340	135	3429	115-3/8	2931	4. ALL DIMN'S 1/8 (3) UNLESS OTHERWISE SHOWN.		
THW-20138-2-4	158-3/8	4023	137-1/2	3493	141	3581	121-3/8	3083	5. DIMENSIONS SHOWN AS: in.(mm)		
THW-20144-2-4	164-3/8	4175	143-1/2	3645	147	3734	127-3/8	3235	CUSTOMER: LOCATION:  ENGINEER : ORDER No.: PROJECT/JOB: LOCATION:  TAG: QUOTE #		
THW-20150-2-4	170-3/8	4328	149-1/2	3797	153	3886	133-3/8	3388			
THW-20156-2-4	176-3/8	4480	155-1/2	3950	159	4039	139-3/8	3540			
THW-20162-2-4	182-3/8	4632	161-1/2	4102	165	4191	145-3/8	3693			